



- 10/100/1000Mbps UTP 5ports
- Unmanaged Ethernet PoE switch
- Port 1 to 4 support PoE (IEEE802.3af/at, Max 60W)
- Port 1 to 4 support 10/100/1000Base-T, auto-sensing
- 100-240V AC Power supply
- 2K MAC Address
- Full-duplex mode, IEEE802.3x flow control
- LED indicator : PWR (Green), Network Link (Yellow), PoE (Green)

Standard	Network Protocol	IEEE 802.3 10Base-TX IEEE 802.3u 100Base-TX/100Base-FX IEEE 802.3ab Gigabit 1000T IEEE 802.3z Gigabit Ethernet Fiber Standard IEEE 802.3x Flow control IEEE 802.3az Energy Efficient Ethernet IEEE 802.3at Power Over Ethernet
	Twisted Pair Transmission	10BASE-T : Cat3,4,5 UTP (≤100meter) 100BASE-TX : Cat5 or later UTP (≤100meter) 1000BASE-T : Cat5e or later UTP (≤100meter)
Interface	UTP Port	Port 1 to 5, 10/100/1000Mbps UTP 5ports (Port 5 uplink)
	POE Port	Port 1 to 4, IEEE802.3af/at (Max 60W)
Capacity	Switching Capacity	10Gbps
	Forwarding Rate	7.44Mpps
	MAC	2K
	Buffer Memory	1M
Physical Parameter	Power Supply	AC input 100-240V 50-60HZ
	Operation TEMP/Humidity	-10 ~ +50°C, 10%~90% RH Non condensing
	Storage TEMP/Humidity	-40 ~ +70°C, 5%~95% RH Non condensing
	Size	220 x 118 x 44 mm (L x H x D)
	Weight	0.63Kg
	Installation	Desktop